



7AH7

7AH7

REMOTE-CUTOFF PENTODE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage. 6.3[□] ac or dc voltsCurrent. 0.15^{□□} ampDirect Interelectrode Capacitances:⁰

Grid No.1 to Plate . . . 0.005 max. μf

Input. 7 μf

Output 6.5 μf

⁰ With external shield connected to cathode.

Mechanical:

Mounting Position. Any

Maximum Overall Length 2-25/32"

Maximum Seated Length. 2-1/4"

Maximum Diameter 1-3/16"

Bulb T-9

Base Lock-in 8-Pin

Basing Designation for BOTTOM VIEW 8V

Pin 1-Heater


Pin 2-Plate

Pin 3-Grid No.2

Pin 4-Grid No.3

Pin 5-Internal

Shield



Pin 6-Grid No.1

Pin 7-Cathode

Pin 8-Heater

Plug - Base
ShellAMPLIFIER - Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE. 300 max. volts

GRID-No.2 (SCREEN) VOLTAGE 300 max. volts

PLATE DISSIPATION. 2 max. watts

GRID-No.2 DISSIPATION. 0.7 max. watt

GRID-No.1 (CONTROL-GRID) VOLTAGE:

Negative bias value. -1 min. volt

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode 90 max. volts

Heater positive with respect to cathode 90 max. volts

Typical Operation and Characteristics:

Plate Voltage. 250 volts

Grid No.3 (Suppressor) Connected to cathode at socket

Internal Shield. Connected to cathode at socket

Grid-No.2 Voltage. 250 volts

Cathode-Bias Resistor#. 250 ohms

Plate Resistance (Approx.) 1 megohm

Transconductance 3300 μhos

Grid-No.1 Bias (Approx.) for

transconductance of 35 μhos -20 volts

Fixed bias not recommended.

□ Nominal voltage = 7.0 volts.

□□ Nominal current = 0.16 ampere.

FEB. 1, 1949

TUBE DEPARTMENT

DATA

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

7AH7



7AH7

REMOTE-CUTOFF PENTODE

Plate Current.	6.8	ma
Grid-No.2 Current.	1.9	ma

FEB. 1, 1949

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA